## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.


## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.



## OPERATING MANUAL: SCTC 1-R/00/02

**HOW TO SET PROGRAMMABLE PARAMETERS**

PROGRAMMABLE PARAMETERS:

S1> FIRST SET VALUE.
S2> SECOND SET VALUE.

**TO ENTER INTO PROGRAM MODE, PRESS "PRG" KEY**

- S1 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S1.
- PRESS "SAVE" TO SAVE PARAMETERS VALUE.
- NOW S2 STARTS BLINKING.
- PRESS "INC" OR "DEC" TO SET VALUE OF S2.
- PRESS "SAVE" TO SAVE VALUE OF S2.

**LED- H INDICATES STATUS OF OUTPUT -1**
**LED- C INDICATES STATUS OF OUTPUT -2**

>SUPPOSE IF YOU SET VALUE S1=5 AND S2=10
>AT STARTING BOTH OUTPUT GOES ON.(H & C)
>IF ACTUAL VALUE REACHES TO 5 OUTPUT –1 GOES OFF.
>IF ACTUAL VALUE REACHES TO 10 OUTPUT –2 GOES OFF.